## Product datasheet



# DALI-2 SENSOR LS/PD C CI

DALI-2 SENSOR LS/PD C CI | Sensors



#### Product family features

- Light and motion sensor for ceiling integration
- Motion detection via passive IR element
- Light sensor operating range: 5...2000 lx (measured at sensor)
- Detection height up to 4 meter
- Function indicator LED

#### Product family benefits

- Motion detection range optimized for corridors
- Simple and fast installation via wire springs
- DALI-2 certified
- DALI Bus powered (No mains connection necessary)
- Multiple sensors connectable to the same DALI line
- Shutter included to optimize sensor detection
- Integreatable in light- and building management systems supporting DALI-2 sensors

#### Areas of application

- Corridor

DALI-2 SENSOR LS/PD C CI


# Product datasheet

## Technical data

## **Electrical data**

Required DALI current (typical)	8 mA
Peak DALI current	8 mA
Maximum start-up time (DALI)	600 ms

## **Dimensions & weight**



Product weight	120.00 g	
Mounting hole spacing, diagonal	68 mm	
Length	105.0 mm	
Width	105.0 mm	
Height	80.5 mm	

## **Temperatures & operating conditions**

Ambient temperature range	-20+45 °C
---------------------------	-----------

## Capabilities

Operating range, light sensor	52000 lx	
Dimming interface	DALI-2	
Detection area	40 m <sup>2 1)</sup>	
Maximum installation height	4 m	
Dimmable	No	
Type of installation	Ceiling integration	

 $^{1)}\,\rm Max.$  distance with elyptic coverage

#### Certificates & standards

Type of protection	IP20

## Product datasheet

## Logistical data

#### **Environmental information**

#### Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration	21-07-2023		
Primary Article Identifier	4052899630451		
Candidate List Substance 1 Lead			
CAS No. of substance 1	7439-92-1		
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
Declaration No. in SCIP database	07063ce6-51bd-478e-9682-1d317e6793a2		

#### Equipment / Accessories

- Optional: Ceiling integration via QBM 220-240 LS/PD CM KIT (IP23)

- Optional: IP54 with Surface mounting KIT

#### Download Data

	File
×	User instruction DALI-2 Sensors LS PD O CI LS PD C CI

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899630451	DALI-2 SENSOR LS/PD C CI	Shipping carton box 24	525 mm x 390 mm x 215 mm	44.02 dm³	6345.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

DALI-2 SENSOR LS/PD C CI