

LFD1300T-G1 -927-04

LINEARlight FLEX DIFFUSE Top White | LED modules for professional and industrial applications
Notice: New Generation or successor products available!



Areas of application

- Individual and customized luminaires
- Organic shaped luminaires
- Architectural Integration – e.g. coves, walls
- Object integration – e.g. handrails
- Signage and illuminated advertising

Product family benefits

- IP67 protection with high performance silicone
- Reliable connection over long periods of time: IP67 connector with built-in protection against liquids penetrating through the wires into the LED strip
- Outdoor use possible: UV and salt mist resistant (UV acc. to ISO 4892-2 - Method A, salt mist acc. to IEC 60068-2-52 severity 1)



Product datasheet

Product family features

- Diffused light lines without visible spots
- Flexible and cuttable module to support design freedom
- Long operational length per single power feed possible (up to 6m)
- Ideal for luminaire designs
- Extra strong self-adhesive backside for easy mounting
- 24 V technology for easy dimensioning
- Recommended in system use with OPTOTRONIC
- Increased reliability due to single piece reel-to-reel technology
- Dimmable with PWM technology

Technical data

Electrical data

| | |
|---|-----------|
| Nominal voltage | 24.0 V |
| Type of current | DC |
| Nominal wattage per meter | 17.8 W |
| Rated wattage | 71.00 W |
| Input voltage range | 23...25 V |
| Accidental reverse input voltage protection up to | 25 V |

Photometrical data

| | |
|--------------------------------------|---------|
| Light color LED | White |
| Color temperature | 2695 K |
| Color rendering index Ra | ≥90 |
| Luminous flux per meter | 1100 lm |
| Total useful luminous flux | 4400 lm |
| Luminous efficacy | 62 lm/W |
| Standard deviation of color matching | ≤3 sdcn |
| Light color (designation) | 2700 K |


Light technical data

| | |
|------------------------------------|----------|
| LED pitch | 7.14 mm |
| Beam angle | 120 ° |
| Rated beam angle (half peak value) | 120.00 ° |
| Starting time | < 0.5 s |
| Warm-up time (60 %) | < 0.50 s |

LED module information

| | |
|----------------------------------|-----|
| Number of LEDs per meter | 140 |
| Number of LEDs per smallest unit | 7 |

Dimensions & weight



| | |
|--|---------------------|
| Length | 4000 mm |
| Length – smallest unit | 50.0 mm |
| Width | 14.1 mm |
| Height | 10.8 mm |
| Cable length | 500.0 mm |
| Product weight | 695.00 g |
| Cable cross-section, input side | 0.5 mm ² |

Colors & materials

| | |
|-----------------------|----------|
| Cover material | Silicone |
| Body material | Silicone |

Temperatures & operating conditions

| | |
|---|----------------------------|
| Performance temp. acc. to IEC 62717 | 50 °C |
| Temperature range in operation at Tc point | -30...80 °C ¹⁾ |
| Ambient temperature range | -30...+50 °C ²⁾ |
| Temperature range at storage | -30...75 °C |

¹⁾ Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

²⁾ Rated ambient temp. 25°C/Providing that temperature at Tc point is below max value during operation/Temperature ramping for environmental testing acc. to IEC 62717, 1K/min

Lifespan

| | |
|--|---------|
| Rated lamp life time | 60000 h |
| Nominal lamp life time | 60000 h |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Number of switching cycles | 30000 |

Capabilities

Product datasheet

| | |
|------------------------------|--------|
| Dimmable | Yes |
| Lowest bending radius | 100 mm |

Certificates & standards

| | |
|--------------------------------|-----------------------------------|
| Energy efficiency class | A |
| Energy consumption | 79 kWh/1000h |
| Standards | CE; ENEC 10 VDE/UL/CSA Recognized |
| Type of protection | IP66/IP67 |

Logistical data

| | |
|-----------------------|--------------|
| Commodity code | 940540399000 |
|-----------------------|--------------|







Product datasheet

Additional product information

- Some LED modules are equipped with a self-adhesive tape for attaching the LED module to suitable materials, such as aluminum profiles, which must be clean and free of oil or silicone coatings, as well as other dirt/dust particles. The adhesive tape is intended for single use and if removed may damage the material to which it is stuck and the LED module itself, which must then be scrapped. Use the adhesive tape when the installation material temperature is in the 18 °C...35 °C range. Complete adhesion takes up to 72 h.
- LED modules are designed for static installations in accordance with IPC 6013C – Use A. Take material vibrations, repetitive torsion, and elongation/compression into account.
- If the operating environment covers a broad temperature range (e.g. outdoor applications) and the operating length is longer than 2 m, the use of adequate mounting surfaces is required. The use of an additional thicker adhesive tape between LED module and mounting surface is also recommended in order to absorb the stress of any mismatch in expansion. Assure enough space for module expansion with increasing temperature.
- The manufacturer is not responsible for damage due to chemical corrosion. The user must provide suitable protection against corrosive agents such as moisture and condensation and any other harmful elements/compounds. Make certain to avoid corrosive atmospheres. According to the current state of LED technology, hydrogen sulfide (H₂S) causes accelerated corrosion which leads to shortened lifetime or premature failure. Sources of H₂S may be rubber, foam rubber, soft-foam tapes, rubber-based sealing, natural sources (e.g. sulfur springs), etc. To avoid H₂S from sulfur-vulcanized rubber use silicon-based materials or peroxide-crosslinked rubber instead. Follow the recommendations in the material datasheet of the rubber supplier.
- IP00 LED modules, as manufactured, have no conformal coating and therefore offer no inherent protection against corrosion. Conformal coating treatment is possible, however materials must be selected properly in order to avoid product damage or impaired performance; the user must also completely seal the cut parts (ends/edges).
- For applications involving exposure to humidity and dust the module must be protected by a fixture or housing with a suitable IP protection class.
- Consult OSRAM Technical Service for further advice.
- Only a qualified electrician may install the module.
- Handle with care and ensure that there is no mechanical product damage, including damage to invisible internal electronics parts.
- Exceeding maximum operating and storage temperature ratings can reduce the expected lifetime or even destroy the LED module. The temperature of the LED module must be measured at the T_c-point in accordance with EN 60598-1 under steady-state conditions, considering the worst case; drive all channels at 100 % power. Refer to the product drawing for the exact location of the T_c-point.
- Exceeding the maximum ratings for the operating voltage causes hazardous overload and will likely destroy the LED module.
- Installation of LED modules and connection to the power supply must comply with all applicable electrical and safety standards.
- Observe correct polarity and wiring diagrams! Incorrect polarity or wrong wiring can cause unpredictable permanent damage or even failure of the product.
- Never exceed the maximum operable length, including daisy-chaining connections.
- Always ensure electrical isolation between the LED module and the mounting surface, especially in the vicinity of connections or cut ends.
- IP00 LED modules are ESD-sensitive; take adequate precautions during installation and operation of the products.
- Use only SELV LED drivers in accordance with applicable lighting standards and LED module ratings. In order to safely operate OSRAM LED modules it is necessary to supply them with an electronically stabilized power supply providing protection against short circuits, overload and overheating. To simplify the approval process of the luminaire/installation, the electronic power supplies control gear for LED modules must bear the CE and ENEC marking. In Europe the Declarations of Conformity must include at least the following standards: EN 61347-2-13, EN 55015, EN 61547 and EN 61000-3-2. ENEC certification will be based on EN 61347-2-13 and EN 62384. OSRAM OPTOTRONIC LED drivers comply with all relevant standards and guarantee safe operation; see the relevant brochure for more detailed information about OSRAM OPTOTRONIC.
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Download Data

Product datasheet

| File | |
|---|--|
|  | User instruction LINEARlight FLEX DIFFUSE |
|  | Product Datasheet LINEARlight FLEX DIFFUSE Top Specification Sheet (EN) |
|  | Brochures Light is freedom of design (EN) |
|  | Certificates VDE-ENEC Certificate |
|  | Eulumdat LFD1300T-G1-927-04 V2 LTD 151220 |
|  | IES data LFD1300T-G1-927-04 V2 IES 151220 |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4062172190770 | LFD1300T-G1 -927-04 | Shipping carton box 6 | 519 mm x 246 mm x 525 mm | 67.03 dm ³ | 11288.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.