

LINEARlight FLEX POWER 3000

LED modules for professional and industrial applications



Areas of application

- Architecture lighting
- Cove lighting
- Ceiling integration

Product benefits

- Large selection of light colors
- Great design freedom thanks to flexibility and cuttability of module
- Simple mounting and connection
- Toolless connection with the optional CONNECTsystem
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back
- High luminous flux
- Extraordinary design and high quality materials
- Type of protection: IP00

Product features

- Flexible and cuttable LED strip
- Luminous flux: up to 3,000 lm/m
- Module efficacy: up to 138 lm/W
- Dimmable with PWM technology
- Fine White (3 SDCM)



Product family datasheet

Technical data

Electrical data

Product description	Nominal voltage	Type of current	Nominal wattage per meter	Rated wattage	Input voltage range	Reverse Voltage
LF3000 -G3-820-03 ¹⁾	24.0 V	DC	28.9 W	86.70 W	23...25 V	25 V
LF3000 -G3-824-03 ¹⁾	24.0 V	DC	28.9 W	86.70 W	23...25 V	25 V
LF3000 -G3-827-03 ¹⁾	24.0 V	DC	23.7 W	71.10 W	23...25 V	25 V
LF3000 -G3-830-03 ¹⁾	24.0 V	DC	23.7 W	71.10 W	23...25 V	25 V
LF3000 -G3-840-03 ¹⁾	24.0 V	DC	21.8 W	65.40 W	23...25 V	25 V
LF3000 -G3-850-03 ¹⁾	24.0 V	DC	21.8 W	65.40 W	23...25 V	25 V
LF3000 -G3-865-03 ¹⁾	24.0 V	DC	21.8 W	65.40 W	23...25 V	25 V
LF3000 -G3-927-03 ¹⁾	24.0 V	DC	28.9 W	86.70 W	23...25 V	25 V
LF3000 -G3-930-03 ¹⁾	24.0 V	DC	28.9 W	86.70 W	23...25 V	25 V
LF3000 -G3-940-03 ¹⁾	24.0 V	DC	26.5 W	79.60 W	23...25 V	25 V
LF3000 -G3-SW30-03 ¹⁾	24.0 V	DC	27.6 W	82.80 W	23...25 V	25 V
LF3000 -G3-SW40-03 ¹⁾	24.0 V	DC	27.6 W	82.80 W	23...25 V	25 V

¹⁾ See product remark

Photometrical data

Product description	Light color LED	Color temperature	Color rendering index Ra	Luminous flux per meter	Total useful luminous flux	Luminous efficacy
LF3000 -G3-820-03 ¹⁾	White	2000 K	>80	2500 lm	7500 lm	87 lm/W
LF3000 -G3-824-03 ¹⁾	White	2400 K	>80	3000 lm	9000 lm	104 lm/W
LF3000 -G3-827-03 ¹⁾	White	2700 K	>80	3000 lm	9000 lm	127 lm/W
LF3000 -G3-830-03 ¹⁾	White	3000 K	>80	3000 lm	9000 lm	127 lm/W
LF3000 -G3-840-03 ¹⁾	White	4000 K	>80	3000 lm	9000 lm	138 lm/W
LF3000 -G3-850-03 ¹⁾	White	5000 K	>80	3000 lm	9000 lm	138 lm/W
LF3000 -G3-865-03 ¹⁾	White	6500 K	>80	3000 lm	9000 lm	138 lm/W
LF3000 -G3-927-03 ¹⁾	White	2700 K	>90	2700 lm	8100 lm	93 lm/W
LF3000 -G3-930-03 ¹⁾	White	3000 K	>90	3000 lm	9000 lm	104 lm/W
LF3000 -G3-940-03 ¹⁾	White	4000 K	>90	3000 lm	9000 lm	113 lm/W
LF3000 -G3-SW30-03 ¹⁾	White	3000 K	>80	3000 lm	9000 lm	109 lm/W
LF3000 -G3-SW40-03 ¹⁾	White	4000 K	>80	3000 lm	9000 lm	109 lm/W

Product description	Light color (designation)
LF3000 -G3-820-03 ¹⁾	Warm Comfort Light
LF3000 -G3-824-03 ¹⁾	Warm Comfort Light
LF3000 -G3-827-03 ¹⁾	Warm White
LF3000 -G3-830-03 ¹⁾	White

Product family datasheet

Product description	Light color (designation)
LF3000 -G3-840-03 ¹⁾	Cool White
LF3000 -G3-850-03 ¹⁾	Daylight
LF3000 -G3-865-03 ¹⁾	Cool Daylight
LF3000 -G3-927-03 ¹⁾	Warm White
LF3000 -G3-930-03 ¹⁾	White
LF3000 -G3-940-03 ¹⁾	Cool White
LF3000 -G3-SW30-03 ¹⁾	Warm White
LF3000 -G3-SW40-03 ¹⁾	White

¹⁾ See product remark

Light technical data

Product description	LED pitch	Beam angle
LF3000 -G3-820-03 ¹⁾	14.3 mm	120 °
LF3000 -G3-824-03 ¹⁾	14.3 mm	120 °
LF3000 -G3-827-03 ¹⁾	14.3 mm	120 °
LF3000 -G3-830-03 ¹⁾	14.3 mm	120 °
LF3000 -G3-840-03 ¹⁾	14.3 mm	120 °
LF3000 -G3-850-03 ¹⁾	14.3 mm	120 °
LF3000 -G3-865-03 ¹⁾	14.3 mm	120 °
LF3000 -G3-927-03 ¹⁾	14.3 mm	120 °
LF3000 -G3-930-03 ¹⁾	14.3 mm	120 °
LF3000 -G3-940-03 ¹⁾	14.3 mm	120 °
LF3000 -G3-SW30-03 ¹⁾	14.3 mm	120 °
LF3000 -G3-SW40-03 ¹⁾	14.3 mm	120 °

¹⁾ See product remark

Product family datasheet

LED module information

Product description	Number of LEDs per meter	Number of LEDs per smallest unit
LF3000 -G3-820-03 ¹⁾	70	7
LF3000 -G3-824-03 ¹⁾	70	7
LF3000 -G3-827-03 ¹⁾	70	7
LF3000 -G3-830-03 ¹⁾	70	7
LF3000 -G3-840-03 ¹⁾	70	7
LF3000 -G3-850-03 ¹⁾	70	7
LF3000 -G3-865-03 ¹⁾	70	7
LF3000 -G3-927-03 ¹⁾	70	7
LF3000 -G3-930-03 ¹⁾	70	7
LF3000 -G3-940-03 ¹⁾	70	7
LF3000 -G3-SW30-03 ¹⁾	70	7
LF3000 -G3-SW40-03 ¹⁾	70	7

¹⁾ See product remark


Dimensions & weight

Product description	Length	Length – smallest unit	Width	Height	Product weight
LF3000 -G3-820-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g
LF3000 -G3-824-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g
LF3000 -G3-827-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g
LF3000 -G3-830-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g
LF3000 -G3-840-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g
LF3000 -G3-850-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g
LF3000 -G3-865-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g
LF3000 -G3-927-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g
LF3000 -G3-930-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g
LF3000 -G3-940-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g
LF3000 -G3-SW30-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g
LF3000 -G3-SW40-03 ¹⁾	3000 mm	100.0 mm	8.0 mm	1.4 mm	39.00 g

¹⁾ See product remark

Product family datasheet

Product line drawing



LF3000 -G3-820-03, LF3000 -G3-824-03, LF3000 -G3-827-03, LF3000 -G3-830-03, LF3000 -G3-840-03, LF3000 -G3-850-03, LF3000 -G3-865-03, LF3000 -G3-927-03, LF3000 -G3-930-03, LF3000 -G3-940-03, LF3000 -G3-SW30-03, LF3000 -G3-SW40-03

Temperatures & operating conditions

Product description	Performance temp. acc. to IEC 62717	Temperature range in operation at Tc point	Ambient temperature range
LF3000 -G3-820-03 ¹⁾	60 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾
LF3000 -G3-824-03 ¹⁾	60 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾
LF3000 -G3-827-03 ¹⁾	55 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾
LF3000 -G3-830-03 ¹⁾	55 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾
LF3000 -G3-840-03 ¹⁾	55 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾
LF3000 -G3-850-03 ¹⁾	55 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾
LF3000 -G3-865-03 ¹⁾	55 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾
LF3000 -G3-927-03 ¹⁾	60 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾
LF3000 -G3-930-03 ¹⁾	60 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾
LF3000 -G3-940-03 ¹⁾	60 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾
LF3000 -G3-SW30-03 ¹⁾	60 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾
LF3000 -G3-SW40-03 ¹⁾	60 °C	-20...90 °C ²⁾	-20...+50 °C ³⁾

¹⁾ See product remark

²⁾ Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

³⁾ Rated ambient temp. 25°C/Providing that temperature at Tc point is below max value during operation/Temperature ramping for environmental testing acc. to IEC 62717, 1K/min

Product family datasheet

Lifespan

Product description	Rated lamp life time	Nominal lamp life time
LF3000 -G3-820-03 ¹⁾	60000 h ²⁾	60000 h
LF3000 -G3-824-03 ¹⁾	60000 h ²⁾	60000 h
LF3000 -G3-827-03 ¹⁾	60000 h ²⁾	60000 h
LF3000 -G3-830-03 ¹⁾	60000 h ²⁾	60000 h
LF3000 -G3-840-03 ¹⁾	60000 h ²⁾	60000 h
LF3000 -G3-850-03 ¹⁾	60000 h ²⁾	60000 h
LF3000 -G3-865-03 ¹⁾	60000 h ²⁾	60000 h
LF3000 -G3-927-03 ¹⁾	60000 h ²⁾	60000 h
LF3000 -G3-930-03 ¹⁾	60000 h ²⁾	60000 h
LF3000 -G3-940-03 ¹⁾	60000 h ²⁾	60000 h
LF3000 -G3-SW30-03 ¹⁾	60000 h ²⁾	60000 h
LF3000 -G3-SW40-03 ¹⁾	60000 h ²⁾	60000 h

¹⁾ See product remark

²⁾ L70/B50 at T_c 40 °C

Capabilities

Product description	Dimmable	Lowest bending radius	Self-adhesive
LF3000 -G3-820-03 ¹⁾	Yes	20 mm	Yes
LF3000 -G3-824-03 ¹⁾	Yes	20 mm	Yes
LF3000 -G3-827-03 ¹⁾	Yes	20 mm	Yes
LF3000 -G3-830-03 ¹⁾	Yes	20 mm	Yes
LF3000 -G3-840-03 ¹⁾	Yes	20 mm	Yes
LF3000 -G3-850-03 ¹⁾	Yes	20 mm	Yes
LF3000 -G3-865-03 ¹⁾	Yes	20 mm	Yes
LF3000 -G3-927-03 ¹⁾	Yes	20 mm	Yes
LF3000 -G3-930-03 ¹⁾	Yes	20 mm	Yes
LF3000 -G3-940-03 ¹⁾	Yes	20 mm	Yes
LF3000 -G3-SW30-03 ¹⁾	Yes	20 mm	Yes
LF3000 -G3-SW40-03 ¹⁾	Yes	20 mm	Yes

Product description	With connection set	With end piece
LF3000 -G3-820-03 ¹⁾	Yes	No
LF3000 -G3-824-03 ¹⁾	Yes	No
LF3000 -G3-827-03 ¹⁾	Yes	No
LF3000 -G3-830-03 ¹⁾	Yes	No
LF3000 -G3-840-03 ¹⁾	Yes	No
LF3000 -G3-850-03 ¹⁾	Yes	No
LF3000 -G3-865-03 ¹⁾	Yes	No
LF3000 -G3-927-03 ¹⁾	Yes	No
LF3000 -G3-930-03 ¹⁾	Yes	No
LF3000 -G3-940-03 ¹⁾	Yes	No

Product family datasheet

Product description	With connection set	With end piece
LF3000 -G3-SW30-03 ¹⁾	Yes	No
LF3000 -G3-SW40-03 ¹⁾	Yes	No

¹⁾ See product remark

Certificates & standards

Product description	Energy efficiency class	Energy consumption	Standards
LF3000 -G3-820-03 ¹⁾	A	95 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
LF3000 -G3-824-03 ¹⁾	A+	95 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
LF3000 -G3-827-03 ¹⁾	A+	78 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
LF3000 -G3-830-03 ¹⁾	A+	78 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
LF3000 -G3-840-03 ¹⁾	A++	72 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
LF3000 -G3-850-03 ¹⁾	A++	72 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
LF3000 -G3-865-03 ¹⁾	A++	72 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
LF3000 -G3-927-03 ¹⁾	A+	95 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
LF3000 -G3-930-03 ¹⁾	A+	95 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
LF3000 -G3-940-03 ¹⁾	A+	88 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
LF3000 -G3-SW30-03 ¹⁾	A+	91 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750
LF3000 -G3-SW40-03 ¹⁾	A+	91 kWh/1000h	CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750

Product description	Type of protection
LF3000 -G3-820-03 ¹⁾	IP00
LF3000 -G3-824-03 ¹⁾	IP00
LF3000 -G3-827-03 ¹⁾	IP00
LF3000 -G3-830-03 ¹⁾	IP00
LF3000 -G3-840-03 ¹⁾	IP00
LF3000 -G3-850-03 ¹⁾	IP00
LF3000 -G3-865-03 ¹⁾	IP00
LF3000 -G3-927-03 ¹⁾	IP00
LF3000 -G3-930-03 ¹⁾	IP00
LF3000 -G3-940-03 ¹⁾	IP00
LF3000 -G3-SW30-03 ¹⁾	IP00
LF3000 -G3-SW40-03 ¹⁾	IP00

Product family datasheet

¹⁾ See product remark

Logistical data

Product description	Temperature range at storage
LF3000 -G3-820-03 ¹⁾	-40...80 °C
LF3000 -G3-824-03 ¹⁾	-40...80 °C
LF3000 -G3-827-03 ¹⁾	-40...80 °C
LF3000 -G3-830-03 ¹⁾	-40...80 °C
LF3000 -G3-840-03 ¹⁾	-40...80 °C
LF3000 -G3-850-03 ¹⁾	-40...80 °C
LF3000 -G3-865-03 ¹⁾	-40...80 °C
LF3000 -G3-927-03 ¹⁾	-40...80 °C
LF3000 -G3-930-03 ¹⁾	-40...80 °C
LF3000 -G3-940-03 ¹⁾	-40...80 °C
LF3000 -G3-SW30-03 ¹⁾	-40...80 °C
LF3000 -G3-SW40-03 ¹⁾	-40...80 °C

¹⁾ See product remark

Product remark

Modules perfectly matched to OSRAM OPTOTRONIC LED drivers (see relevant table)/For current photometric data and important safety, installation and application information, see www.osram.com/led-systems/All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values

Equipment / Accessories

- Simplified connection with optional matching CONNECTsystem
- Quick installation with optional SLIM TRACK System
- Perfectly matched to OPTOTRONIC 24 V electronic control gears

Application advice















For more detailed application information and graphics please see product datasheet.

Sales and Technical Support

Sales and Technical Support www.osram.com

Download Data

Product family datasheet

File	
	User instruction LINEARlight FLEX POWER
	Product Datasheet LINEARlight FLEX POWER Specification Sheet (EN)
	Brochures Light is freedom of design (EN)
	Certificates EAC Certificate
	Certificates UL Certificate
	Certificates ENEC10_VDE Certificate
	Certificates VDE_ENEC+ Certificate
	Certificates CB TEST CERTIFICATE DE1-57844
	Declarations of conformity EU Declaration of conformity
	Declarations of conformity Manufacturer declaration
	Eulumdat 727191_LF3000-G3-820-03_LDT
	IES data 727190_LF3000-G3-820-03_IES
	Eulumdat 727193_LF3000-G3-824-03_LDT
	IES data 727192_LF3000-G3-824-03_IES
	Eulumdat 727195_LF3000-G3-827-03_LDT
	IES data 727194_LF3000-G3-827-03_IES
	Eulumdat 727197_LF3000-G3-830-03_LDT
	IES data 727196_LF3000-G3-830-03_IES
	Eulumdat 727199_LF3000-G3-840-03_LDT
	IES data 727198_LF3000-G3-840-03_IES
	Eulumdat 727201_LF3000-G3-850-03_LDT
	IES data 727200_LF3000-G3-850-03_IES

Product family datasheet

	Eulumdat 727203_LF3000-G3-865-03_LDT
	IES data 727202_LF3000-G3-865-03_IES
	Eulumdat 727205_LF3000-G3-927-03_LDT
	IES data 727204_LF3000-G3-927-03_IES
	Eulumdat 727207_LF3000-G3-930-03_LDT
	IES data 727206_LF3000-G3-930-03_IES
	Eulumdat 727209_LF3000-G3-940-03_LDT
	IES data 727208_LF3000-G3-940-03_IES
	Eulumdat 727211_LF3000-G3-SW30-03_LDT
	IES data 727210_LF3000-G3-SW30-03_IES
	Eulumdat 727213_LF3000-G3-SW40-03_LDT
	IES data 727212_LF3000-G3-SW40-03_IES

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899952911	LF3000 -G3-820-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g
4052899952928	LF3000 -G3-824-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g
4052899952935	LF3000 -G3-827-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g
4052899952942	LF3000 -G3-830-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g
4052899952959	LF3000 -G3-840-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g
4052899952966	LF3000 -G3-850-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g
4052899952973	LF3000 -G3-865-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g
4052899963948	LF3000 -G3-927-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g

Product family datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899963955	LF3000 -G3-930-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g
4052899963962	LF3000 -G3-940-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g
4052899963979	LF3000 -G3-SW30-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g
4052899963986	LF3000 -G3-SW40-03	Shipping carton box 8	241 mm x 195 mm x 205 mm	9.63 dm ³	1245.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Accessories Optional

Product description	Accessory name	Accessory code
LF3000 -G3-820-03	FX -SC08-G2-CT2PF-0500	▶ 4052899464735
LF3000 -G3-820-03	FX -SC08-G2-CT2PF-1000	▶ 4052899464766
LF3000 -G3-820-03	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF3000 -G3-824-03	FX -SC08-G2-CT2PF-0500	▶ 4052899464735
LF3000 -G3-824-03	FX -SC08-G2-CT2PF-1000	▶ 4052899464766
LF3000 -G3-824-03	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF3000 -G3-827-03	FX -SC08-G2-CT2PF-0500	▶ 4052899464735
LF3000 -G3-827-03	FX -SC08-G2-CT2PF-1000	▶ 4052899464766
LF3000 -G3-827-03	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF3000 -G3-830-03	FX -SC08-G2-CT2PF-0500	▶ 4052899464735
LF3000 -G3-830-03	FX -SC08-G2-CT2PF-1000	▶ 4052899464766
LF3000 -G3-830-03	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF3000 -G3-840-03	FX -SC08-G2-CT2PF-0500	▶ 4052899464735
LF3000 -G3-840-03	FX -SC08-G2-CT2PF-1000	▶ 4052899464766
LF3000 -G3-840-03	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF3000 -G3-850-03	FX -SC08-G2-CT2PF-0500	▶ 4052899464735
LF3000 -G3-850-03	FX -SC08-G2-CT2PF-1000	▶ 4052899464766
LF3000 -G3-850-03	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF3000 -G3-865-03	FX -SC08-G2-CT2PF-0500	▶ 4052899464735
LF3000 -G3-865-03	FX -SC08-G2-CT2PF-1000	▶ 4052899464766
LF3000 -G3-865-03	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF3000 -G3-927-03	FX -SC08-G2-CT2PF-0500	▶ 4052899464735
LF3000 -G3-927-03	FX -SC08-G2-CT2PF-1000	▶ 4052899464766
LF3000 -G3-927-03	FX -SC08-G2-CT4PJ	▶ 4052899464858

Product family datasheet

LF3000 -G3-930-03	FX -SC08-G2-CT2PF-0500	4052899464735
LF3000 -G3-930-03	FX -SC08-G2-CT2PF-1000	▶ 4052899464766
LF3000 -G3-930-03	FX -SC08-G2-CT4PJ	▶ 4052899464858
LF3000 -G3-940-03	FX -SC08-G2-CT2PF-0500	▶ 4052899464735
LF3000 -G3-940-03	FX -SC08-G2-CT2PF-1000	▶ 4052899464766
LF3000 -G3-940-03	FX -SC08-G2-CT4PJ	▶ 4052899464858

References / Links

System configurator tool is available online at <https://flex.osram.info/en/flex-configurator>

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.