

## OT FIT 50/220...240/300 D L

OPTOTRONIC FIT D L | Linear / Area Constant Current – Non dimmable



### Areas of application

- Linear lighting for office, education, industry, storage areas and retail
- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for installation in emergency lighting systems according to EN 60598-2-22
- Suitable for luminaires of protection class I

### Product family benefits

- Small housing design
- Fixed current
- Lifetime: up to 100,000 h (temperature at  $T_c = 65\text{ }^\circ\text{C}$ , max. 10 % failure rate)
- High quality of light thanks to low output ripple current
- High efficiency
- Fulfill safety requirement due to overload, overtemperature, Hot Plug protection

### Product family features

- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Versatile scope of application due to output power range of up to 50 W
- Supply voltage: 220...240 V
- Available with output current range: up to 350 mA
- Non-isolated drivers

## Technical data

### Electrical data


Nominal input voltage	220...240 V
Mains frequency	50...60 Hz
Input voltage AC	198...264 V <sup>1)</sup>
Input voltage DC	176...276 V
Current set	Fixed current
Total harmonic distortion	< 20 %
Power factor $\lambda$	> 0.95
ECG efficiency	>90 %
Device power loss	5.0 W <sup>2)</sup>
Protective conductor current	<2.0 mA
Max. ECG no. on circuit breaker 10 A (B)	35
Max. ECG no. on circuit breaker 16 A (B)	56
Max. ECG no. on circuit breaker 25 A (B)	89
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Nominal output voltage	54...175 V
U-OUT (working voltage)	< 250 V
Nominal output current	300 mA <sup>3)</sup>
Output current tolerance	$\pm 10$ %
Output ripple current (100 Hz)	< 10 %
Nominal output power	16.2...52.5 W
Galvanic isolation	Non isolated

<sup>1)</sup> Permitted voltage range

<sup>2)</sup> Maximum

<sup>3)</sup>  $\pm 5$  %

## Dimensions & weight



Mounting hole spacing, length	200.0 mm
Product weight	125.00 g
Cable cross-section, input side	0.5...1.5 mm <sup>2</sup>
Cable cross-section, output side	0.5...1.5 mm <sup>2</sup>
Wire preparation length, input side	8.5...9.5 mm
Wire preparation length, output side	8.5...9.5 mm
Length	210.0 mm
Width	30.0 mm
Height	21.0 mm

## Colors & materials

Casing material	Metal
-----------------	-------

## Temperatures & operating conditions

Ambient temperature range	-15...+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 %

## Lifespan

ECG lifetime	50000 / 100000 h <sup>1)</sup>
--------------	--------------------------------

<sup>1)</sup> At maximum T<sub>c</sub> = 75°C / 10% failure rate / At T<sub>c</sub> = 65°C / 10% failure rate

## Additional product data

Encapsulated	No
--------------	----

## Capabilities

## Product datasheet

<b>Dimmable</b>	No
<b>Overheating protection</b>	Automatic reversible
<b>Overload protection</b>	Automatic reversible
<b>Short-circuit protection</b>	Automatic reversible
<b>No-load proof</b>	Yes
<b>Max. cable length to lamp/LED module</b>	2.0 m
<b>Suitable for fixtures with prot. class</b>	I
<b>Suitable for emergency lighting</b>	Yes
<b>Type of connection, output side</b>	Push terminal
<b>Number of channels</b>	1






### Certificates & standards

<b>Approval marks – approval</b>	CE / EL / VDE-EMC / ENEC 10 / CCC / RCM
<b>Standards</b>	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 62384/Acc. to EN 62386
<b>Protection class</b>	I
<b>Type of protection</b>	IP20

### Logistical data

<b>Temperature range at storage</b>	-25...85 °C
<b>Commodity code</b>	850440829000

### Download Data

File	
	Product Datasheet 728917_OT FIT 50220240300 D L
	Certificates VDE EMC Certificate 40011668
	Certificates VDE ENEC Certificate 40038085
	Certificates CCC Certificate 2017171002001468
	Declarations of conformity EU Declaration of Conformity 3366459

### Logistical Data

## Product datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899469884	OT FIT 50/220...240/300 D L	Shipping carton box 20	234 mm x 161 mm x 101 mm	3.81 dm <sup>3</sup>	2665.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.